

# EBPW

## PLASTIC WEATHERPROOF BATTERY UNIT

The EBPW battery unit incorporates a rugged plastic enclosure with 5VA flame-retardant, fastened with stainless steel screws for enhanced corrosion resistance. Its slim, streamlined design facilitates straightforward installation. Two fully adjustable, glare-free, round light heads deliver consistent emergency illumination.



### FEATURES AND SPECIFICATIONS

#### CIRCUITRY




- LED ultra bright light source
- 120-347 VAC input
- Maintenance free, 3.6V Ni-cad battery
- Wet location
- IP65
- Operating temperature: 0°C to +40°C

#### MECHANICAL

- High impact thermoplastic construction
- Test switch and battery charging indicator
- Complete battery recharge in 24 hours
- Ceiling mount, Wall mount
- Fully adjustable, LED heads are standard

#### APPROVALS

- CSA 22.2 No. 141

OVERVIEW			
<b>LIGHT SOURCE</b>	LED	<b>DURATION</b>	120 MINS
<b>INPUT VOLTAGE (V AC)</b>	120-347	<b>LUMENS</b>	180 LUMENS TOTAL
  			

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.

## TECHNICAL SPECIFICATION TABLE

PART NUMBER	SERIES	NUMBER OF HEADS	LAMP [W]	LIGHT SOURCE	INPUT VOLTS [V AC]	COLOUR
5000011	EBPW-WHT	2	1	LED	120-347	WHITE

## SPACING GUIDE

MOUNTING HEIGHT (FT)	SPACING CENTER TO CENTER (FT)
8	26.5
10	24
15	19.5

## DIMENSIONS

