

EBW

WEATHERPROOF

BATTERY UNIT

The EBW weatherproof battery unit is a compact, robust assembly engineered for reliable operation in wet-location environments. Its flame-retardant enclosure incorporates smooth, modern contours optimized to accommodate a wide range of installations.



FEATURES AND SPECIFICATIONS

CIRCUITRY

- LED ultra bright light source
- 120-347 VAC input
- Maintenance free, 7.2V Ni-cad battery
- Wet location
- IP65
- Cold Weather temperature: -25°C to +50°C

MECHANICAL

- High impact thermoplastic construction
- Brownout and short circuit protection
- Test switch and battery charging indicator
- Complete battery recharge in 24 hours
- Universal mounting
- Fully adjustable, LED heads are standard

APPROVALS

- CSA 22.2 No. 141

OVERVIEW

LIGHT SOURCE	LED	DURATION	120 MINS
INPUT VOLTAGE [V AC]	120-347	LUMENS	600 LUMENS TOTAL

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions.
All products are subject to change or may be discontinued any time without notice.

TECHNICAL SPECIFICATION TABLE

PART NUMBER	SERIES	NBR OF HEADS	LAMP (W)	LIGHT SOURCE	INPUT VOLTS (V AC)	COLOUR	OPTION
5000014	EBW-WHT-CW	2	1	LED	120-347	WHITE	COLD WEATHER

SPACING GUIDE

MOUNTING HEIGHT (FT)	SPACING CENTER TO CENTER (FT)
8	67
10	64
15	58

DIMENSIONS

