

Project _____
Catalogue n° _____

Type _____
Date _____

AimLite

RMWP

WEATHERPROOF REMOTE

The RMWP weatherproof remotes are a robust solution engineered for reliable operation in wet-location environments. Their polycarbonate housing and fully adjustable, glare-free heads ensure optimal performance in any application.

FEATURES AND SPECIFICATIONS



MECHANICAL

- LED ultra bright light source
- 3-12 V DC
- Polycarbonate housing
- Aluminum canopy
- Wet location
- IP65
- Ceiling mount, Wall mount
- Fully adjustable, LED heads are standard
- Operating temperature: -25°C to +50°C

APPROVALS

- CSA 22.2 No. 141



OVERVIEW			
LIGHT SOURCE		LED	LUMENS
			100 LUMENS PER HEAD
DC VOLTAGE (V DC)		3-12	
<div><div><div>65</div><div>IP</div><div>RATING</div></div><div><div></div><div>WET LOCATION</div></div><div></div></div>			

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions.
All products are subject to change or may be discontinued any time without notice.

TECHNICAL SPECIFICATION TABLE

PART NUMBER	SERIES	DC VOLTS (V DC)	NBR OF HEADS	LAMP (W)	LIGHT SOURCE	COLOUR
5000009	RMWP1	3-12	1	1	LED	WHITE
5000010	RMWP2	3-12	2	2	LED	WHITE

SPACING GUIDE

MOUNTING HEIGHT (FT)	SPACING CENTER TO CENTER (FT)
8	27
10	26
15	20

DIMENSIONS

