

VPL4-L GEN. 2

3 CCT AND 3 POWER SELECTABLE, NEMA 4X, NSF VAPOR TIGHT OPTIONAL EMERGENCY REMOTE



This 4' luminaire ideal for a variety of industrial and commercial applications. Installed either indoors or outdoors, the VPL4-L provides superior light distribution and is intended for environments where moisture and/or dust may be present. Perfect for applications requiring the complete containment of LEDs for easy washability and hose down. The VPL4-L series can withstand reduced temperatures and moderate impact.

FEATURES & SPECIFICATIONS

CONSTRUCTION

Physical Characteristics

- Lightweight, slim and durable impact-resistant polycarbonate construction
- Easy installation and maintenance. Gear tray is attached to the lens exposing the internal components when the fixture is in open position. Change the color temperature and desired lumen output with the simple touch of a button
- Uniform gasketed seal and reinforced stainless steel clips block the ingress of moisture and dust
- Pre-drilled end-holes and two watertight glands are offered with each fixture to preserve integrity of internal components

Mounting options

Surface (ceiling/wall), suspended or 90° surface mounting. Set of 2 V-hooks and 2 stainless steel mounting clips included with each

fixture for surface or suspended mounting with chain or aviation cable

Lens

The frosted LED diffusing pigment lens provides uniform light distribution and has been UV stabilized to ensure that there is no yellowing over time. This impact-resistant polycarbonate lens is impervious to rust or rot and is unaffected by extreme temperatures.

PERFORMANCE DATA

- Available in 3 500/4 000/5 000 K selectable color temperature
- 80+ CRI
- Electrical ratings: 120-347 V
- Estimated life of over 54 000 to L70
- 0-10 V dimming driver. Dimming cables sold separately, see ordering guide
- 2 kV surge protection [standard].

See options table for additional surge protection.

- Operating temperature: -40°C to +40°C [-40°F to +104°F]
DL: 0°C to +25°C [32° to 77°F]
BRIDGE:
-40°C to +40°C [-40°F to 104°F]
(when 65 W in ceiling mount, operating temperature with BRIDGE is
-40°C to +35°C / -40°F to +95°F)

OPTIONAL EMERGENCY LIGHTING

Normally ON LED Vapor Tight Luminaire "BRIDGE"

- Consuming 11 W, 12-24 VDC
- 200 mA constant current
- Delivers 1216-1346 lumens in emergency mode
- Ease of maintenance when used with AimLite emergency lighting battery units complete with auto test function
- Complements AimLite's Normally ON LED Vapor Tight family

- Patent pending
Please view the BRIDGE specification section for more details on this technology

EMERGENCY LIGHTING COMPLIANCES

- CSA certified as a C22.2 C141-15 emergency lighting luminaire
- Meets ICES-005 requirements

GENERAL LIGHTING COMPLIANCES

- Suitable for damp & wet locations
- IP66
- Meets requirements of ICES-005 [Class B]
- UL1598, UL8750
- cETLus certified
- cCSAus
- NSF certified (Splash Zone and Non Food Zone)
- NEMA 4X
- IK10
- DLC Premium & DLC Standard
- BC Hydro

OVERVIEW			
LIGHT SOURCE	LED	COLOR TEMPERATURE [K]	3 CCT (3 500/4 000/5 000 K)
WATTS [W]	30/45/65	CRI	80+
LUMEN OUTPUT [LM]	4 439 - 9 001	WEIGHT [LBS]	5.2
EFFICACY [LM/W]	133 - 147		

Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC Qualified Products List at www.designlights.org/search.

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.

VPL4-L GEN. 2

QUICK SHIP ORDERING GUIDE



PART NUMBER	WATTS	VOLTS	COLOR TEMP.	LUMEN OUTPUT	EFFICACY	CRI	LIFE L70	TESTED HOURS LM-80	DIMMING	PF	THD
	[W]	[V AC]	[K] ¹	[LM] ^{2,3}	[LM/W]		[HRS] ⁴	[HRS] ⁴			[%]
VPL4-PS65B-32-3C	30/45/65	120-347	3 500/4 000/5 000	4 439/6 385/9 001	145	80+	> 54 000	190 000	0-10 V	>0.9	<20

¹ Typical color temperature range: +/- 5 %

² Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %

³ Lumen values are based on 4 000 K default programming. Please refer to the LUMEN SPECIFICATION TABLE for more details on other color temperatures

⁴ Life hours are derived from IESNA LM-80 testing report and projected per IESNA TM-21 extrapolations

DLC UNIQUE ID TABLE

PART NUMBER	DLC PREMIUM UNIQUE ID ¹	DLC STANDARD UNIQUE ID ²	DLC STANDARD UNIQUE ID ³
VPL4-PS65B-32-3C	S-V3LBZJ	S-QJ7F54	S-VFYM3Q

¹ Primary Use Designation: Stairwell and Passageway Luminaires

² Primary Use Designation: Direct Linear Ambient Luminaires

³ Primary Use Designation: Low-Bay Luminaires for Commercial and Industrial Buildings

ORDERING GUIDE

VPL4	PS65B		3C	/
SERIES	LUMEN PACKAGE [W]	VOLTS [V]	COLOR TEMP. [K]	OPTIONS
VPL4	PS65B - 30/45/65	32 - 120-347 2 - 120-277 ⁴	3C - 3 500 4 000 5 000	BLANK - NO SENSOR OS ^{1,3} - OCCUPANCY SENSOR DIM1 ² - 5 WIRE CABLE FOR AC AND 0-10 V DIMMING EL1 ⁷ - 1 BRIDGE NORMAL ON EMERGENCY REMOTE DL ^{3,6} - EMERGENCY BACK UP (0°C - 25°C) 120 V, 120-277 V KV - 10 KV SURGE PROTECTOR L6 - 6' WHITE POWER CORD L10 - 10' WHITE POWER CORD L6-BK - 6' BLACK POWER CORD L10-BK - 10' BLACK POWER CORD CH ³ - CENTER HOLE 7/8" AC ^{2,5} - AVIATION CABLE KIT PVM - PIVOT MOUNT BRACKETS (SURFACE MOUNT CEILING AND WALL)

¹ To see available options, please consult the occupancy sensors section

² When selecting AC or DIM1 option, please also select cable option whether L6, L10, L6-BK or L10-BK. DL option not compatible with DIM1

³ When selecting CH, OS (external) and DL options, the fixture maintains wet location status, however NEMA 4X and IP rating are not applicable

⁴ Only available for luminaires when used with DL option

⁵ Aviation cable length based on selected power cable length

⁶ Fixture functional in AC mode, when power goes off emergency driver (DL) powers LED boards. One emergency driver per fixture is standard

⁷ The BRIDGE Emergency Power conversion module is compatible with all the following configurations: PS42B and PS65B.

Not compatible with the following options: DL, OS (external). When in Emergency Mode, unit only consumes 11 watts

For Emergency Lighting spacing, please see p.5

LUMEN SPECIFICATION TABLE

PART NUMBER	WATTS	VOLTS	3 500 K		4 000 K		5 000 K	
			LUMEN OUTPUT [LM]	EFFICACY [LM/W]	LUMEN OUTPUT [LM]	EFFICACY [LM/W]	LUMEN OUTPUT [LM]	EFFICACY [LM/W]
VPL4-PS65B-32-3C	30	120-347	4 278	142	4 439	147	4 288	142
	45	120-347	6 154	136	6 385	142	6 169	137
	65	120-347	8 675	133	9 001	138	8 696	133

DEFAULT PROGRAMMING

VPL4-PS65B-32-3C: 65 W / 4 000 K

VPL4-L GEN. 2

PRODUCT FEATURES


Slider button for the Color Temperature and Power Select feature

Lightweight, slim and high impact resistant polycarbonate construction

Stainless Steel Clips and Safety Straps support the Lens and Gear Tray to the Housing during installation and maintenance

Gear Tray attached to Lens for easy installation and maintenance

ACCESSORIES (INCLUDED IN THE BOX)



SURFACE MOUNTING AND V-HOOKS (SET OF 2)




HARDWARE KIT

ACCESSORIES (ORDER SEPARATELY)


PART NUMBER	TYPE	COMPATIBLE WITH
CAS984-SMVH-KIT	REPLACEMENT SURFACE MOUNTING BRACKETS AND V-HOOKS (SET OF 2PCS)	ALL CONFIGURATIONS
CAS984-ANG90-KIT	90° ANGLE BRACKETS (SET OF 2PCS)	ALL CONFIGURATIONS
CAS984-4-SMVH-KIT	TAMPER PROOF BRACKETS (SET OF 2PCS)	ALL CONFIGURATIONS
BKT926-4FT ¹	JUNCTION BOX BRACKET (SET OF 1PC)	ALL CONFIGURATIONS
LEN409-4	4FT REPLACEMENT FROSTED POLYCARBONATE LENS	ALL CONFIGURATIONS
CAS1015-4-LATCH	STAINLESS STEEL REPLACEMENT LATCH KIT WITH HOLE (SET OF 10PCS)	ALL CONFIGURATIONS
CAS1023-HW	REPLACEMENT HARDWARE KIT: WATERTIGHT END CAPS (2PCS), WATERTIGHT GLANDS (2PCS), SURFACE MOUNT BRACKETS (2PCS), V-HOOKS (2PCS) AND MOUNTING HARDWARE	ALL CONFIGURATIONS
HAR-1182-WGLAND-GY	REPLACEMENT WATERTIGHT GLAND (1PC)	ALL CONFIGURATIONS
HAR-1182-CPLUG-GY	REPLACEMENT WATERTIGHT END CAP (1PC)	ALL CONFIGURATIONS
HAR1144-1	VANDAL RESISTANT SCREWS (10PCS)	ALL CONFIGURATIONS
HAR1144-BIT	BIT FOR VANDAL RESISTANT SCREW (1PC)	HAR1144-1

¹ Accessory requires additional center hole [CH] on top of housing. Fixture maintains wet location status, however NEMA 4X and IP ratings are not applicable with CH. Please see installation instructions for more details



90° ANGLE BRACKETS (SET OF 2)

TAMPER PROOF BRACKETS (SET OF 2)



JUNCTION BOX BRACKET (SET OF 1)



REPLACEMENT FROSTED POLYCARBONATE LENS

REPLACEMENT LATCH KIT WITH HOLE (SET OF 10)



REPLACEMENT WATERTIGHT GLAND (1PC)

REPLACEMENT WATERTIGHT END CAP (1PC)

SMART ACCESSORIES (SOLD SEPARATELY)

PART NUMBER	TYPE	COMPATIBLE WITH
CTRL-KBC1-001	GENIO BLUETOOTH® MESH INTERNAL INTEGRATED FIXTURE ADAPTER	ALL CONFIGURATIONS
OSI-MW105E, CTRL-KBC1-001	GENIO BLUETOOTH® MESH KIT INTERNAL HIGH FREQUENCY SENSOR (OSI-MW105E) AND INTEGRATED FIXTURE ADAPTER [CTRL-KBC1-001]	ALL CONFIGURATIONS

VPL4-L GEN. 2

BRIDGE TECHNICAL SPECIFICATION TABLE

LUMEN PACKAGE	WATTS	BRIDGE WATTS [W]	3 CCT (3 500/4 000/5 000 K)
	[W]		LUMEN OUTPUT [LM]
PS65B	30	11	1 216
	45		
	65		

OCCUPANCY SENSORS

ON-OFF SENSORS

Detection - On at [Detection Area] % during [Hold Time] min. Off

PART NUMBER	POSITION	VOLTS [V]	TECHNOLOGY	HEIGHT [FT]	DETECTION AREA [%]	HOLD TIME [MIN]	DAYLIGHT MIN LEVEL [LUX]	REMOTE ¹	LOCATION ² [°C]
OSE-PO-0301	EXTERNAL	120-347	PIR	20-40	100	20	N/A		DRY, -10° TO +40°C
OSE-PO-0302	EXTERNAL	120-347	PIR	20-40	100	20	N/A		DRY, -40° TO +40°C
OSE-PO-0501	EXTERNAL	120-347	PIR	15-40	100	15	3 000	OSI-FSIR-100	DRY, -10° TO +40°C
OSE-PO-0502	EXTERNAL	120-347	PIR	15-40	100	15	3 000		DRY, -10° TO +40°C
OSE-PO-0701	EXTERNAL	120-277	PIR	20	100	15	N/A		WET, -40° TO +40°C
OSI-FO-1601	INTERNAL	120-277	HIGH FREQUENCY	20	100	10	DISABLE	OSI-RC100	DRY AND WET, -40° TO +40°C
OSI-FO-1701	INTERNAL	120-347	HIGH FREQUENCY	13	100	10	DISABLE		DRY AND WET, -20° TO +40°C

BI-LEVEL SENSORS

Detection - On at [Detection Area] % during [Hold Time] min., then [Stand-by Dim level] %

PART NUMBER	POSITION	VOLTS [V]	TECHNOLOGY	HEIGHT [FT]	DETECTION AREA [%]	HOLD TIME [MIN]	STAND-BY DIM LEVEL [%]	DAYLIGHT MIN LEVEL [LUX]	REMOTE ¹	LOCATION ² [°C]
OSE-FB-0402	EXTERNAL	120-347	HIGH FREQUENCY	50 MAX.	100	20	30	50	OSI-RC-MH10	WET, -35° TO +40°C
OSI-FB-1601	INTERNAL	120-277	HIGH FREQUENCY	20	100	10	50	DISABLE	OSI-RC100	DRY AND WET, -40° TO +40°C
OSI-FB-1602	INTERNAL	120-277	HIGH FREQUENCY	20	100	10	30	DISABLE	OSI-RC100	DRY AND WET, -40° TO +40°C
OSI-FB-1701	INTERNAL	120-347	HIGH FREQUENCY	13	100	10	50	DISABLE		DRY AND WET, -20° TO +40°C
OSI-FB-1702	INTERNAL	120-347	HIGH FREQUENCY	13	100	10	30	DISABLE		DRY AND WET, -20° TO +40°C

TRI-LEVEL SENSORS

Detection - On at [Detection Area] % during [Hold Time] min., then [Stand-by Dim level] % during [Stand-by period] min. Off

PART NUMBER	POSITION	VOLTS [V]	TECHNOLOGY	HEIGHT [FT]	DETECTION AREA [%]	HOLD TIME [MIN]	STAND-BY DIM LEVEL [%]	STAND-BY PERIOD [MIN]	DAYLIGHT MIN LEVEL [LUX]	REMOTE ¹	LOCATION ² [°C]
OSE-FT-0402	EXTERNAL	120-347	HIGH FREQUENCY	50 MAX.	100	30	30	10	50	OSI-RC-MH10	WET, -35° TO +40°C
OSI-FT-1601	INTERNAL	120-277	HIGH FREQUENCY	20	100	10	30	30	DISABLE	OSI-RC100	DRY AND WET, -40° TO +40°C
OSI-FT-1602	INTERNAL	120-277	HIGH FREQUENCY	20	100	10	30	30	50	OSI-RC100	DRY AND WET, -40° TO +40°C
OSI-FT-1701	INTERNAL	120-347	HIGH FREQUENCY	13	100	10	30	30	DISABLE		DRY AND WET, -20° TO +40°C
OSI-FT-1702	INTERNAL	120-347	HIGH FREQUENCY	13	100	10	30	30	50		DRY AND WET, -20° TO +40°C

¹ To be ordered separately

² Min and max ambient temperature of the fixture with the specific sensor. Please verify fixture temperature on the first page for compatibility with sensor

For more settings visit

www.aimlite.com/documentation/technical-information/

VPL4-L GEN. 2


COMPATIBLE DIMMERS¹

BRAND	MODEL
LEVITON	DS710-10Z, DD710-BDZ, IP710-LFZ
LUTRON	DVSTV-453P, MAESTRO MS-Z101

Dimming range: 10 %-100 %

¹ This table shows dimmers that have been tested and have demonstrated proper operation under normal conditions. Each installation being unique, various factors such as load, common neutrals or other electrical products on the circuit can, in certain instances, cause variance in system performance. Read and comply to the dimmer installation instructions. Consult dimming system manufacturer for additional support in operation. Some dimmers may require more than one product for stable operation. AimLite recommends to use dimmers designed to work with LED products. Older dimmers designed for incandescent products may cause erratic operation.

DIMENSIONS



BRIDGE


NORMALLY ON EMERGENCY REMOTE LUMINAIRE

This unit can be used with an emergency backup powered by either a 12 V or 24 V DC AimLite battery unit, complete with or without auto test.

NORMAL MODE



EMERGENCY MODE



TYPICAL SPECIFICATION

Supply and install AimLite “ Bridge” ___FT, LED vapor tight, Model number: _____ remote normally on emergency luminaire, CSA C22.2 141-15 certified and meet the requirements prescribed by ICES-005 . Normally on when AC is present and when connected to a AimLite battery unit complete with or without auto test , the fixture shall act as an Emergency Lighting remote and consume 11W of DC power in ___ V producing 1316 to 1408 Lumens in Emergency mode.

The remote normally on emergency luminaire shall be powered by a AimLite emergency lighting battery unit as described herein and shown on the drawings. The AimLite Auto Diagnostic micro-controller board shall supply the rated load for a minimum of a 1/2 hour to 87.5% of the rated battery voltage. The unit shall be rated 120V, 277V or 347V, 60 Hz and be CSA listed. The unit shall have an output of: ___V and ___W.

The charge voltage factory set to $\pm 1\%$ tolerance. High efficiency, rapid recovery, precision control charging system shall be employed to promote long battery life and reduce the potential for grid corrosion. The charger shall provide a continuous high charge to recharge the battery, when the battery is at full capacity, the charger will shut-off. Periodically the charger shall provide a pulse of energy to keep the battery topped off. The pulse charger shall be precisely regulated and shall charge the battery in relation to its temperature, state or charge and input voltage fluctuations. The charger shall be current limited, temperature compensated, short-circuit proof and reverse polarity protected. The unit shall be furnished with an electronic lockout circuit, which will connect the battery when the AC circuit is activated, and an electronic brownout circuit, which will activate the emergency lights when utility power dips below 75% of nominal voltage. A low voltage battery protection circuit shall be provided and will disconnect the load when the battery reaches the end of discharge.

The automated testing performed by the AimLite Auto-Test system has been designed to comply with all of the requirements of the National Fire Code. Every month a 5 minute discharge and diagnostic test checks the operational status of the unit. Every 12 months this test is extended to the full 30 minute, Code required duration. This insures that the battery charger is recharging the battery in accordance with Code requirements. The unit shall be AimLite model: SL_ _____


VPL4-L GEN. 2

BRIDGE

NORMALLY ON EMERGENCY REMOTE LUMINAIRE



BRIDGE WIRING DIAGRAM



LEGEND



AC wires



Connected to the dedicated lighting circuit



DC wires



BRIDGE Factory Installed

COMMERCIAL LIGHTING	FOOT SPACING
VPL4-L GEN. 2	42 foot spacing ¹


¹ Applicable for 8', 10' or 12' ceilings

VPL4-L GEN. 2

PHOTOMETRIC DATA¹

VPL4-PS65B-32-3C • 30 W • 4 000 K • 4 702 LM

POLAR CANDELA DISTRIBUTION



ZONAL LUMEN SUMMARY


ZONE	LUMENS	% FIXTURE
0-30	1 065.4	22.7
0-40	1 745.7	37.1
0-60	3 127.9	66.5
60-90	1 273.7	27.1
70-100	888.3	18.9
90-120	269.8	5.7
0-90	4 401.6	93.6
90-180	300.4	6.4
0-180	4 702.0	100

ILLUMINANCE AT A DISTANCE

CENTER BEAM FC			BEAM WIDTH	
1.7'	477		4.5'	7.3'
3.3'	127		8.7'	14.2'
5.0'	55.2		13.1'	21.4'
6.7'	30.7		17.6'	28.7'
8.3'	20.0		21.8'	35.6'
10.0'	13.8		26.2'	42.9'
■ Vert. Spread: 105.3° ■ Hor. Spread: 130°				

VPL4-PS65B-32-3C • 45 W • 4 000 K • 6 818 LM

POLAR CANDELA DISTRIBUTION



ZONAL LUMEN SUMMARY


ZONE	LUMENS	% FIXTURE
0-30	1 544.8	22.7
0-40	2 531.2	37.1
0-60	4 535.5	66.5
60-90	1 846.9	27.1
70-100	1 288.1	18.9
90-120	391.2	5.7
0-90	6 382.3	93.6
90-180	435.5	6.4
0-180	6 817.9	100

ILLUMINANCE AT A DISTANCE

CENTER BEAM FC			BEAM WIDTH	
1.7'	692		4.5'	7.3'
3.3'	184		8.7'	14.2'
5.0'	80.0		13.1'	21.4'
6.7'	44.5		17.6'	28.7'
8.3'	29.0		21.8'	35.6'
10.0'	20.0		26.2'	42.9'
■ Vert. Spread: 105.3° ■ Hor. Spread: 130°				

VPL4-PS65B-32-3C • 65 W • 4 000 K • 9 509 LM

POLAR CANDELA DISTRIBUTION



ZONAL LUMEN SUMMARY

ZONE	LUMENS	% FIXTURE
0-30	2 154.4	22.7
0-40	3 530.2	37.1
0-60	6 325.3	66.5
60-90	2 575.7	27.1
70-100	1 796.4	18.9
90-120	545.5	5.7
0-90	8 901.0	93.6
90-180	607.4	6.4
0-180	9 508.5	100

ILLUMINANCE AT A DISTANCE

CENTER BEAM FC			BEAM WIDTH	
1.7'	956		4.5'	7.3'
3.3'	256		8.7'	14.2'
5.0'	112		13.1'	21.4'
6.7'	62.1		17.6'	28.7'
8.3'	40.5		21.8'	35.6'
10.0'	27.9		26.2'	42.9'
■ Vert. Spread: 105.3° ■ Hor. Spread: 130°				

¹ Complete IES files available on our website.