

AimLite

PST LED ROUND POST TOP

CCT AND 3 POWER SELECTABLE
7 PIN RECEPTACLE AND SHORTING CAP



FEATURES

- Die-cast aluminum housing comes standard in a black powder coated finish
- All configurations come standard with a 7 pin receptacle and shorting cap
- Easy access to color temperature and power select switch
- The post top arm accommodates 2-3/8" and 3" tenons and Slipfitter and Square/Round pole arm comes as accessories
- Type V distribution that provides wide uniform lightoutput



Square/Round pole mounting
(sold separately)



Slipfitter mounting
(sold separately)



AimLite

PST

T 514 227-1288

TF 1 866 348-2374

aimlite.com

PART NO	WATTS	VOLTS	COLOR TEMP.	LUMEN OUTPUT	EFFICACY	CRI	LIFE L70	DISTRIBUTION TYPE	B.U.G.	EPA	FINISH	DIMMING	PF	THD	MASTER CASE QTY
	[W]	[VAC]	[K] ¹	[LM] ^{2,3}	[LM/W]		[HRS] ⁴			[FT ²]		[YES/NO]		[%]	
PSTPS755323CBKPR7	50/60/75	120-347	30/40/50K	6 750/8 100/ 10 125	135	80+	50 000	Type V	B3-U0-G3	1.48	Black	Yes	0.90	20	1
PSTPS1505322CBKPR7	100/120/150	120-347	40/50K	13 500/16 200/20 200	135	80+	50 000	Type V	B3-U0-G3	1.48	Black	Yes	0.90	20	1

¹ Typical color temperature range: +/- 5 %.

² Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %.

³ Lumen values are based on 4 000 K default programming. Please refer to the LUMEN SPECIFICATION TABLE for more details on other color temperatures.

⁴ Life hours are derived from IESNA LM-80-08 testing report and projected per IESNA TM-21-11 extrapolations.

DLC UNIQUE ID TABLE

PART NO	DLC PREMIUM UNIQUE ID ¹
PSTPS755323CBKPR7	S-R432DQ
PSTPS1505322CBKPR7	S-8C32FQ

¹ Primary Use Designation: Outdoor Pole/Arm-Mounted Area and Roadway Luminaires

ACCESSORIES (ORDER SEPARATELY)

PART NO	TYPE
CAS1011-SWIVEL-BK	Slipfitter
CAS1011-RNDSQBK	Square/Round pole arm



SLIPFITTER



SQUARE/ROUND POLE ARM

CHANGE YOUR MOUNTING TYPE IN 3 SIMPLE STEPS¹

Step 1: Remove the post top arm



Step 2: Choose the desired mounting



Slipfitter



Square/Round pole arm

Step 3: Install the new luminaire onto the pole.



¹ Refer to the installation instruction for more details