

CRVE

PLASTIC COMBO RUNNING MAN

LOW PROFILE MODERN DESIGN



The CRVE Combo is a low-profile thermoplastic running man sign. Designed and built to ensure performance and reliability. The modern design of the CRVE Combo has smooth rounded corners and a shallow contour to compliment any interior design.

FEATURES & SPECIFICATIONS

CIRCUITRY

- LED ultra bright light source
- 120/277/347 VAC input
- High-output MR16 LED technology
- Fully automatic, current limiter charger
- Maintenance free, Ni-MH battery
- Low voltage disconnect protection
- Dry location
- Operating temperature: +10°C to +25°C
- Auto-test available

MECHANICAL

- High impact thermoplastic construction
- Universal faces
- Ceiling mount and Wall mount
- White colour is standard
- Fully adjustable, LED heads are standard

APPROVALS

- CSA 22.2 No. 141-15

OVERVIEW			
LIGHT SOURCE	LED	SIGN EMERGENCY POWER CONSUMPTION [W]	2
INPUT VOLTAGE [V AC]	120/277/347	OUTPUT CAPACITY [W]	25-50
SIGN POWER CONSUMPTION [W]	2		
<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>LED</p> </div> <div style="text-align: center;">  <p>ICES 005</p> </div> <div style="text-align: center;">  <p>SP® Energy Verified Energie Verifiee</p> </div> </div>			

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.

TYPICAL SPECIFICATION



TYPICAL SPECIFICATION

Supply and install Aimlite's CRVE High impact thermoplastic Running Man and Battery combination unit. The sign shall operate from 120/277/347 V AC Input. The sign shall be suitable for wall or ceiling mount and come complete with 3 Running Man fibers for universal direction. The frame and back plate shall be high impact, UV stabilized, thermoplastic construction and offer quick snap faceplates and universal canopy for rapid and simple installation. The combination unit shall be 120/277/347 V AC, suitable for dry locations, suitable for an ambient temperature 10°C to 25°C, provide a minimum of 30 minutes emergency power duration and consist of two 12v 2, 5, or 7 W LED heads. The unit shall be temperature compensated, maintenance free, Ni-MH battery. The unit shall be CSA C22.2 C141-15 certified and ICES compliant. The Aimlite Sign and Battery combination unit shall be CRVE _____

TECHNICAL SPECIFICATION TABLE

PART NUMBER	DC VOLTS (V DC)	WATTS	NBR OF FACE	NBR OF HEADS	LAMP (W)	LIGHT SOURCE	INPUT VOLTS (V AC)	COLOUR	OPTION
CRVE1225U-2MD2	12	25	UNIVERSAL	2	2	LED	120/277/347	WHITE	
CRVE1225U-2MD2/ATD	12	25	UNIVERSAL	2	2	LED	120/277/347	WHITE	AUTO TEST
CRVE1225U-2MD5	12	25	UNIVERSAL	2	5	LED	120/277/347	WHITE	
CRVE1225U-2MD5/ATD	12	25	UNIVERSAL	2	5	LED	120/277/347	WHITE	AUTO TEST
CRVE1225U-2MD7	12	25	UNIVERSAL	2	7	LED	120/277/347	WHITE	
CRVE1225U-2MD7/ATD	12	25	UNIVERSAL	2	7	LED	120/277/347	WHITE	AUTO TEST
CRVE1250U-2MD2	12	50	UNIVERSAL	2	2	LED	120/277/347	WHITE	
CRVE1250U-2MD2/ATD	12	50	UNIVERSAL	2	2	LED	120/277/347	WHITE	AUTO TEST
CRVE1250U-2MD5	12	50	UNIVERSAL	2	5	LED	120/277/347	WHITE	
CRVE1250U-2MD5/ATD	12	50	UNIVERSAL	2	5	LED	120/277/347	WHITE	AUTO TEST
CRVE1250U-2MD7	12	50	UNIVERSAL	2	7	LED	120/277/347	WHITE	
CRVE1250U-2MD7/ATD	12	50	UNIVERSAL	2	7	LED	120/277/347	WHITE	AUTO TEST

DIMENSIONS

