

RPTB TRITIUM SIGN



The AimLite RPTB series of self-luminous running man signs provide reliable signage for applications where typical signs cannot be employed. The RPTB series are completely non-electrical so they can be installed in any location, including glass entranceways/vestibules, greenhouses and outdoor applications. This also insures that the RPTB signs are non-sparking, making them ideal for explosion-proof locations. RPTB signs are not governed by the requirements of the C860 standard due to the non-electrical design of the light source.

FEATURES & SPECIFICATIONS

LIGHT SOURCE

- 15 year expected life
- The tubes are lined with phosphor which glows green in color
- The light output is unaffected by extremes temperature or moisture
- Continuously illuminate at performance specifications for the rated duration
- Minimum initial brightness at time of manufacture of 0.15 foot lambert. Brightness variation between letters does not exceed a ration of 3 to 2

MECHANICAL

- Tritium signs are supplied standard with a white, low profile thermoplastic frame
- The frame secures the thermoplastic face and stencil and allows for simple wall mounting
- Bracket for ceiling mounting included

- The tritium is sealed within several silicate tubes fitted into the ABS thermoplastic housing
- The light source requires no maintenance or service throughout the lifespan of the sign
- Temperature from -30°C to +65°C

COMPLIANCE

- Running Man Multipurpose signs are compliant to the CAN/ULC-S572 standard

OVERVIEW

LIGHT SOURCE

TRITIUM



FOR COMPLETE WARRANTY DETAILS, PLEASE SEE OUR TERMS AND CONDITIONS ON OUR WEBSITE.

ORDERING GUIDE


SERIES	LIFE EXPECTANCY (YEARS)	NBR OF FACES	MOUNTING	COLOR	OPTION
RPTB	15Y - 15 YEARS	1 - SINGLE FACE 2 - DOUBLE FACE	UM - UNIVERSAL MOUNT PM - PENDANT MOUNT ¹	WHT - WHITE (STANDARD) BLK - BLACK GRY - GREY	WGD - WIREGUARD ²

¹ Pendant mount option available only with white finish.


² Wireguard only available for single face wall mounted configurations.

DIMENSIONS

UNIVERSAL MOUNT



PENDANT MOUNT



CONFIGURATIONS



Comes standard with three pictogram legends for direction selection.